



WEVER & DUCRÉ
LIGHTING

SOLID petit 1.0

133564K5

GENERAL

Ceiling

Surface

Jet Black + Gold

IP20

Interior

350 lm

9005^a

LED

3000 K

PHYSICAL

Diameter 60 mm

Height 130 mm

0.32 kg

ELECTRICAL

incl. PS | phase-cut dim

220 - 240 V

Total connected power 4.5 W

PC1

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project

Type

Notes

Quantity

Date





WEVER & DUCRÉ
LIGHTING

SOLID petit 1.0

133564K5

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.92	0.88	0.83	0.79	0.76
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.