



WEVER & DUCRÉ
LIGHTING

DEEP IP44 1.0 PAR16

112620B0C

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Recessed

Jet Black

IP44

Interior

280 lm

9005^a

LED

Lamp PAR16

PAR16

Socket GU10

max. 12 W

2700 K

CRI 90

OPTICAL

Wide Flood

Beam angle 47°

PHYSICAL

Diameter 95 mm

Height 102 mm

0.3 kg

Blade Springs

ELECTRICAL

100 - 240 V

Total connected power 8.6 W

PC2

Safety distance 0.3 m

CUTOUT

Diameter 86-89 mm

Min. ceiling thickness 8 mm


Max. ceiling thickness 25 mm

Recessed depth 105 mm


^a RAL Palette colors may deviate slightly due to production conditions.



IP44 $\pm 0,3$



LIGHT DISTRIBUTION



112620B0C The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for September 24, 2020 the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.



WEVER & DUCRÉ
LIGHTING

DEEP IP44 1.0 PAR16

112620B0C

CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	418	0.89
2	105	1.78
3	46	2.66
4	26	3.55
5	16	4.44

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø · H (MM)	ORDERCODE
2700K GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 3
3000K GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 5
2700K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 2
2700K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 3
3000K GU10	Signal White	ø50-58	9 0 1 2 2 8 W 4

PAR16 LED Lamp | Ambient

TYPE	Ø · H (MM)	ORDERCODE
1800-2850K GU10	ø50-58	9 0 1 2 2 9 S 9