



WEVER & DUCRÉ  
LIGHTING

# DEEPER IP44 1.0 PAR16

152220B0

Project
Type
Notes
Quantity
Date

## GENERAL

Ceiling  
 Recessed  
 Jet Black  
 IP44  
 Interior  
 270 lm  
 9005<sup>a</sup>

## LED

Lamp PAR16  
 PAR16  
 Socket GU10  
 max. 12 W  
 2700 K  
 CRI 90

## OPTICAL

Wide Flood  
 Beam angle 47°

## PHYSICAL

Diameter 85 mm  
 Height 112 mm  
 0.15 kg


## ELECTRICAL

100 - 240 V  
 Total connected power 8.6 W  
 PC2  
 Safety distance 0.3 m


## CUTOUT

Diameter 76-79 mm  
 Min. ceiling thickness 4 mm  
 Max. ceiling thickness 38 mm  
 Recessed depth 115 mm

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# DEEPER IP44 1.0 PAR16

152220B0

## CONE DIAGRAM

wide flood 48°

h (m)	EO° (lx)	ø (m)
1	398	0.89
2	99	1.78
3	44	2.66
4	24	3.55
5	15	4.44

## LED LAMPS

### PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K   GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 3
3000K   GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 5
2700K   GU10	Signal White	ø50-58	9 0 1 2 2 8 W 2
2700K   GU10	Signal White	ø50-58	9 0 1 2 2 8 W 3
3000K   GU10	Signal White	ø50-58	9 0 1 2 2 8 W 4

### PAR16 LED Lamp | Ambient

TYPE	Ø·H (MM)	ORDERCODE
1800-2850K   GU10	ø50-58	9 0 1 2 2 9 S 9