



WEVER & DUCRÉ
LIGHTING

STIPO 1.0

737157D4

Project

Type

Notes

Quantity

Date

GENERAL

Floor
Surface
Dark Grey Texture
IP65
Exterior
450 lm

LED

3000 K
CRI 80
L70 / 50000 h
3-step binning

PHYSICAL


Diameter 52 mm
Height 164 mm
0.5 kg
Tilt min 135°
Tilt max 135°

ELECTRICAL


220 - 240 V
Total connected power 7.3 W
PC2
Safety distance 0.3 m



IP65 □ ↺ ↻ ↻↻0,3↻↻



LIGHT DISTRIBUTION



[737157D4] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

STIPO 1.0

737157D4

GROUND SPIKE

Ground Spike

| TYPE | Ø · H (MM) | ORDERCODE |
|-------------------|------------|-----------------|
| STAKE 1.0 STIPO | ∅122 · 357 | 9 0 0 1 3 1 0 6 |