

Product Code 10-9733-05-CL Installation Instructions Photometry Dialux | ULD Revit (BIM)



### Invisible Adjustable

Francesc Vilaró

Bollard IP54 Invisible Adjustable LED 10.7 LED warm-white 3000K ON-OFF Black 469lm

#### Technical features

Luminaire total power: 10.7W

Real lumens: 469 Real Im/W: 44

Correlated Colour Temperature (CCT): LED warm-white 3000K

Lens / reflector angle: HORIZONTAL 111°

Structure material: Aluminium

Structure finish: Black

Diffuser material: Polycarbonate

Diffuser finish: Opal

Voltage / frequency: 100-240V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.90

Useful life: 50,000h L80B20

Warranty: 5 años

Resistant to marine environments: Yes













#### Luminotechnic features


CRI: 80


MacAdam steps: 3

Photobiological risk: RGO UGR crosswise: 25.2

UGR lengthwise: 25.0

Lampholder	Quantity	Light source power (W)	Correlated Colour Temperature (CCT)
LED	1	9W	LED warm- white 3000K








Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 10-9733-05-CL Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



# Invisible Adjustable

Francesc Vilaró

Bollard IP54 Invisible Adjustable LED 10.7 LED warm-white 3000K ON-OFF Black 469lm

### Logistics



x 12

Net weight (kg): 0.49

Packaged weight (kg): 0.91

Packaging: 120mm x 50mm x 600mm

### Light application



Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 10-9733-05-CL Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



# Invisible Adjustable

Francesc Vilaró

Bollard IP54 Invisible Adjustable LED 10.7 LED warm-white 3000K ON-OFF Black 469lm

#### Accessories included



IP67 Driver & Connector



Spiked post

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.