

Product Code 05-2705-14-14

Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



# Lia LED 600mm

Wall fixture Lia LED 600mm LED 26.2 LED warm-white 3000K ON-OFF White 1798lm

#### Technical features

Luminaire total power: 26.2W

Real lumens: 1798 Real lm/W: 69

Correlated Colour Temperature (CCT): LED warm-white 3000K

Lens / reflector angle: HORIZONTAL 136°

Structure material: Steel Structure finish: White

Diffuser material: Polycarbonate

Diffuser finish: Opal

Voltage / frequency: 100-240V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.90

Useful life: 50,000h L80B20

Warranty: 5 años













### Luminotechnic features

CRI: 80

MacAdam steps: 3

Photobiological risk: RG1

UGR crosswise: 21.3 UGR lengthwise: 15.5

| Lampholder | Quantity | Light<br>source<br>power<br>(W) | Correlated<br>Colour<br>Temperature<br>(CCT) |
|------------|----------|---------------------------------|--|
| LED        | 1        | 23.1W                           | LED warm-<br>white 3000K                     |






Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 05-2705-14-14

Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



## Lia LED 600mm

Packaging: 660mm x 100mm x

130mm

Wall fixture Lia LED 600mm LED 26.2 LED warm-white 3000K ON-OFF White 1798lm

# Logistics x 6 Net weight (kg): 1.37 Packaged weight (kg): 1.99

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.