

Product Code 05-2703-14-14

Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Lia LED 250mm

Wall fixture Lia LED 250mm LED 8.8 LED warm-white 3000K ON-OFF White 544lm

Technical features

Luminaire total power: 8.8W

Real lumens: 544 Real lm/W: 62

Correlated Colour Temperature (CCT): LED warm-white 3000K

Lens / reflector angle: HORIZONTAL 135°

Structure material: Steel Structure finish: White

Diffuser material: Polycarbonate

Diffuser finish: Opal

Voltage / frequency: 100-240V/50-60Hz

Dimming protocol: ON-OFF

Power Factor: 0.50

Useful life: 50,000h L80B20

Warranty: 5 años













Luminotechnic features

CRI: 80

MacAdam steps: 3

Photobiological risk: RG1

UGR crosswise: 18.8 UGR lengthwise: 14.1

| Lampholder | Quantity | Light source power (W) | Correlated Colour Temperature (CCT) |
|------------|----------|---------------------------------|--|
| LED | 1 | 6.7W | LED warm- white 3000K |








Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.



Product Code 05-2703-14-14 Installation Instructions 3D File Photometry Dialux | ULD Revit (BIM)



Lia LED 250mm

| Wall fixture Lia LED 250mm LED 8.8 LED warm-white 3000K ON-OFF White 544lm | | | |
|---|--|--|--|
| Logistics | | | |
| Net weight (kg): 0.68 Packaged weight (kg): 1.01 Packaging: 310mm x 100mm x 130mm | | | |
| | | | |
| | | | |
| | | | |

Image may not match reference. LedsC4 reserves the right to amend any of the product's components. The data related to flux, power and colour temperature may be subject to changes made by the manufacturer.