

ODREY WALL 1.5


387320GB0

GENERAL
Wall, Surface
Gold + Black Matt
IP20
Interior
Indirect 0 lm
Direct 340 ^a to 350 ^b lm
Total 340ª to 350 ^b lm
CIE flux code: 94 98 100 100 73
. ==
LED
Lamp PAR16
Socket GU10
max. 12.0 W
2700 K ^a , 3000 K ^b
CRI ≥ 90
ELECTRICAL
ELECTRICAL
100 - 240 V
LED Inset 6.5 W
Class 1

(4)

X

Wall surface luminaire made from die-cast aluminium; surface Gold + Black Matt wet painted; matt tex $ture; up \ or \ down \ light \ emission; lamp \ socket \ GU10; lamp \ type \ PAR16; max. \ 12W; 100 - 240 \ V; degree \ of \ proposition \ p$ tection IP20; PC1; lamp not included;




G

Ε

PHYSICAL

Diameter 115 mm Height 245 mm $0.36 \, \mathrm{kg}$

LIGHT DISTRIBUTION



a PAR16 LAMP 2700K CRI90

b PAR16 LAMP 3000K CRI90



ODREY WALL 1.5

387320GB0

LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Black	Ø50·60	901228B3
3000K >90 CRI GU10	Black	Ø50·60	901228B5
2700K >90 CRI GU10	White	Ø50·60	901228W3
3000K >90 CRI GU10	White	Ø50·60	901228W5
2700K >80 CRI GU10	Silver	Ø50·60	90522782
3000K >80 CRI GU10	Silver	ø50·60	9 0 5 2 2 7 S 4